

To be completed by Verifier

Project Information				
Verifier Name		Date of Verification:	Initial Meter Reading =	
System Owner Name		Project Name (if different from S	System Owner name)	
Installation Address				
Trade Ally Name		Wind Turbine mfg., model		
A.	General Requirements			
	Site receives service from PGE or Pacific Pov	ver [verify on meter or customer l	oill, fatal]	
	System meets net metering requirements [ver Manual, correction]	ification that net-metering agreer	ment in process or complete in	
	Installation is of workmanlike quality [visual inspection using judgment, comment/correction]			
	System is properly permitted and has approve Permit Type & Approval Date: Permit Type & Approval Date: Other Permit:	ed final inspections [verify if prese	ent & approved, correction]	
B.	Materials			
	Materials used outdoors are sunlight/UV-resis materials using judgment, correction]	stant and listed for outdoor location	ons [visual inspection of	
	Materials used are designed to withstand the inspection using judgment, comment/correction		hey are exposed [visual	
	Dissimilar metals that have galvanic action (sinspection using judgment, correction]	uch as aluminum and steel) are is	solated from one another [visual	
	Aluminum is not in direct contact with concrete	e materials [visual verification of	contact, correction]	
	High-quality fasteners appropriate for the environment/correction]	ironment have been used [visual	inspection using judgment,	
C.	Wind System Equipment and Installation	on		
	Wind turbine and inverter are as specified on application in Manual, correction to records/fa		ation [verification with	
	All components are new [visual inspection usi	ng judgment, comment/correction	n]	
	Inverter, turbine and tower have 5 year manuf	facturer warranties [verify in custo	omer manual, correction/fatal]	
	Bottom of the turbine rotor appears to be 30 for [visual inspection using judgment, comment/c		within 400 feet of the System	
	System appears to be set back from all power Release has been signed) and habitable build rotor radius [visual inspection using judgment	lings a distance equal to or great		

energytrust.org



To be completed by Verifier

Wind turbine is not mounted on a pre-existing structure [visual verification, fatal]
Equipment includes lightning protection and surge suppression [visual verification using judgment, correction]
Raceway on the tower is of equipment grounding type. If conductors are run directly inside the tower or leg, the tower is certified as a raceway. [visual inspection, comment/correction]
Wire size and type appear to comply with manufacturer requirements [visual inspection using judgment, correction/fatal]
Tower has been engineered to accommodate the wind turbine at the site [visual inspection of tower documentation, fatal]
Foundation has been engineered to accommodate the load of the wind turbine and tower given the site's soil conditions [visual inspection of foundation design, fatal]
Tower is a minimum of 70 feet tall [visual inspection, fatal]
Guyed tower turnbuckles are secured by lacing with the guywire or a cable no smaller than the guywire [visual verification, correction]
Lay-down area for tilt-up tower is clear of permanent vegetation or structures [visual inspection of site, comment]
Tower appears to be straight and plumb [visual inspection using judgment, correction]
Permanent safety signage is posted on the tower indicating that the tower is a risk [visual inspection for sign, comment/correction]
Junction boxes are listed and suitable for the environment [visual inspection using judgment, comment/correction]
Permanent labels are applied to components as required by code [visual verification of labels, comment/correction]
Disconnect switch coverplates are secured closed in a way that requires a tool to open [verification of security, comment/correction]
Hardware and structural members for non-tower elements are either hot-dip galvanized steel, coated or painted steel (not ok for coastal sites), corrosion-resistant aluminum or stainless steel [visual inspection of materials, comment/correction]
Clearances for all equipment are per manufacturer specifications [verify with installation manual, comment/correction]
Diversion load(s) are clearly identified as a heat source by a permanent label [visual verification of label, correction]
Components are mounted securely [physical inspection for movement, comment/correction]
Equipment has not been modified so that the listing or warranty is voided [visual inspection using judgment, comment/correction]
AC/DC disconnects have been installed so that the inverter and output circuits can be safely isolated and removed. If the disconnection means is not within sight from the utility meter, the location is identified on the utility meter. [verification of disconnects, correction]
Disconnection means used can be switched under load without an arcing hazard. Pull-out style disconnecting means have not been used [visual verification of equipment, correction]
Electrical terminations are torqued to spec, secured, and strain-relieved appropriately. Wire ends have been coated with anti-corrosive compound prior to termination. [visual & physical inspection for security and coating, comment/correction]

energytrust.org



To be completed by Verifier

	Cables, raceway, exposed conductors, and electrical boxes are secured and supported according to code and in accordance with their performance ratings. Those on the tower are supported for a vibration environment. [visual inspection of security and movement using judgment, comment/correction]
	Twist-on wire connectors have not been used on DC conductors or ground wires, or any conductors on the tower. Wire connections have been made with mechanical wire splicing devices. If outdoors or exposed to moisture, wire connectors are listed for wet locations and mounted to prevent moisture from being trapped in the connector. [visual inspection of connections, correction]
	Revenue quality electric meter is installed on the AC output side of the inverter(s) or controller and appears to be properly installed and operating correctly [visual inspection of meter, correction]
	Meter(s) are identified with a permanent label as "Wind Turbine Output." If located outdoors, this label is UV-resistant. [visual inspection of meter(s), correction]
C2.	Battery-based System (if applicable)
	Batteries are located in a secure enclosure that meets seismic requirements and is weatherproof, as needed [visual inspection of enclosure, correction]
	Access to live battery terminals has been limited per Oregon Electrical Specialty Code [visual inspection that enclosure requires tool to open, correction]
	If used, flooded lead acid batteries are housed in an enclosure with adequate spill containment and vented to the outdoors, with a nearby, clearly marked safety kit [visual inspection of enclosure and safety kit, correction]
	Battery connections and inverter cables appear to be properly sized, with secured crimps and lugs on ends [visual inspection of connections, correction]
	Components for which a temperature compensation option is available appear to have been installed per manufacturer instructions to control battery charge properly [visual inspection of settings and manufacturer instructions, correction]
	If the turbine may produce voltages that could damage the System in the absence of grid power, controller(s) and diversion load(s) have been installed and properly adjusted per Oregon Electrical Specialty Code [visual inspection of diversion equipment, correction]
	AC output meter appears to be of the 5-jaw type, and correctly wired to meter power flows to both utility and AC loads [visual inspection of meter, correction]
D.	Wind Monitoring Equipment and Installation (if applicable)
	Monitoring equipment has at least a one-year warranty [verify warranty in customer manual, correction]
	Data logger is mounted to allow convenient data recovery or is connected to internet [visual inspection using judgment, correction]
	If located outside or in a wet environment, the data logger is mounted in a weather-tight enclosure [visual inspection using judgment, correction]
	Wind monitor appears to be mounted one rotor diameter below the turbine hub and at least three feet away from any point of the tower. The sensor is neither directly upwind nor directly downwind of the turbine tower. [visual inspection of location, comment/correction]
E.	System Operation and Performance
	Turbine and components appear to be operating properly. There are no movements or sounds that seem unusual or inappropriate. [visual & auditory inspection using judgment, comment/correction]



To be completed by Verifier

F.	Customer Manual
	Customer manual is present and includes each of the following sections [visual inspection of manual, comment/correction]
	Section 1 — System Design and Operation
	System Overview Page: Form 721: Small Wind System Overview or an equivalent overview page summarizes the System's operating conditions and provides emergency information.
	Operation & Maintenance Instructions: Installer's written instructions for System start-up and shut-down procedure, troubleshooting guidelines and recommended routine maintenance schedule. For battery-based systems, includes operation, maintenance and safety procedures for batteries and charge controller.
	Electrical As-built Diagram: Schematic diagram that accurately depicts all electrical components installed, including:
	Major components, with specifications listed
	Power conductor and equipment ground wire types and sizes
	Raceway types and sizes
	Length of wire runs
	Applicable subpanel(s), main service panel and utility connection
	AC and DC overcurrent protection device types and sizes
	Any planned or existing generation inputs (e.g. wind, solar, micro-hydro)
<u>Ц</u>	Site Plan: Diagram showing layout, including indication of lay-down area for tilt-down tower.
	Mechanical Design: Description of wind turbine and tower, including engineering specifications of structural elements, foundation blueprints and manufacturer installation instructions.
	Upgrades, Modifications, Repairs & Service: Documentation and/or area for future documentation of all field modified settings, software upgrades, repairs, performed maintenance and other System changes.
	Section 2 — Warranties and Installation Documentation
	Contractor Warranty: Program trade ally's 2-year minimum full System warranty covering labor, workmanship and materials.
	Manufacturers' Warranties: Written warranties and product registration instructions for wind turbine, inverter(s) and other primary components. Inverter, turbine and tower must have 5 year manufacturer warranties.
	Incentive Application: Final version of the signed form showing incentive and System configuration approved by Energy Trust.
	Permit(s): Copy of approved electrical and building permits and final inspection reports for the System.
	Utility Net Metering Agreement: Copy of the agreement between the utility customer and the utility.
	Section 3 — Manuals and Data Sheets
	Parts and Source List: If not documented elsewhere, bill of material listing all System components including part numbers. If feasible, inverter and wind turbine serial numbers shall be recorded to facilitate replacement in the case of product recall or recovery in the case of theft.
	Inverter Owner's Manual: Documentation from inverter manufacturer.
	Wind Turbine Owner's Manual: Documentation from turbine manufacturer.



To be completed by Verifier

	Fower & Foundation Documentation: Documentation of tower and foundation from tower manufacturer.	
	Wind Monitoring System Owner's Manual (if applicable): Documentation from wind monitoring System manufacturer.	
	Manufacturer Data Sheets or Manuals for Major Components: Including but not limited to: charge controller, controller, diversion load, batteries, disconnect switches, ground fault protection equipment, lubricants, and lightning arrestors, unless covered in the manuals listed above.	
G.	Owner Education	
	Owner understands basic system operation [interview using judgment, comment]	
	Owner can accurately read meter [interview using judgment, comment]	
	Owner understands potential performance impacts of objects within 300 feet of turbine [interview using judgment, comment]	
	Owner understands required inspections and maintenance [interview using judgment, comment]	
	Owner knows whom to call in the case of an emergency [interview using judgment, comment]	
	Owner understands proper electrical and mechanical shut-down and start-up procedure [interview using judgment, comment]	
	Owner understands how to operate and collect data from the wind monitoring equipment [interview using judgment, comment]	
Guide	e to bracketed items:	
	in brackets explain how the inspector determines if a requirement has been met, and the action required by ade ally to pass inspection if the requirement hasn't been met. [means of inspection, result]	
Comm	nent — Improvements are recommended for future installations.	
Correction — Correction is required before incentive can be issued.		
Fatal — A fatal flaw with the project that is believe to be un-correctable. Project is unlikely to be eligible for incentives.		
Notes	2.	
Notes	5.	